NTT01

24 Hour Compact Immersion Heater Timeswitch

Features & Benefits

- 96 Quick-Set Segments for up to 48 ON/48 OFF Programmes Per 24 Hrs
- Red LED 'Mains ON' and Green LED 'Output' Indicators For Easy Viewing
- 'Traffic Light' Slide Switch for Easy ON (green),
 Auto (green & red) and OFF (red) Mode Indication
- Switches ON and OFF at Preset Times
- Easy to Use Captive Segment Dial
- Permanent ON/OFF Control
- Fits a Standard Flush or Surface Mount Box min 32mm



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface Mount
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP20
Setting Type	Segment
Back Box Minimum Depth (mm)	32
Program Modes	24 Hour
Mounting Hole Centres (mm)	60
Standby Consumption	<1.43W

Data sheet **NTT01**

Time / Immersion & General Purpose Timeswitches

Number Of Channels	1
Switch Rating	16A Resistive 6A Inductive, 100W LED
Shortest Switching Time	15 Minutes
Programmable Slots	48 ON 48 OFF (96 Segments)
Permanent ON Facility	Yes (Slider Switch)
Cable Capacity (mm2)	1.5 - 2.5mm2 ² Flexible Cable
Cable Entry(s)	Back Entry

General

160
92
92
60
Polycarbonate
White
Fittings (Rawl Plugs, Screws)
5012483012291
3 Years
9032890090

Line Diagrams





