

# SLB2300

## 2300W PIR Light Controller – Black

### Features & Benefits

- Pan and tilt feature
- Light ON times adjustable
- LUX (light level) adjustment – Day to Night
- Manual ON/OFF switching override
- IP55 weatherproof rating
- Simple and quick to fit terminal block connectors
- Corner mounting bracket available – SLBCB (Sold Separately)



### Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface
Earth Class Rating	Class I
Operating Temperature	-20°C to 40°C
Ingress Protection Rating	IP55
Setting Type	Dial
Approved Mounting Height (m)	2.5
Motion Detection (m)	12
Detection Angle	180°
Pan & Tilt Adjustment	90° Left/Right From Centre, Tilt 15° (Up), 60° (Down)
Mounting Hole Centres (mm)	50
Standby Consumption	<1W

# Data sheet

## SLB2300

Light / PIR Lighting Controllers

<b>Number Of Channels</b>	1
<b>Switch Rating</b>	250W LED, 500W Fluorescent, 2300W Halogen
<b>ON Time Adjustment</b>	5 Seconds to 15 Minutes. User Adjustable
<b>LUX Level</b>	5 to 1000
<b>Detection Range (m)</b>	12
<b>Permanent ON Facility</b>	Yes (Pulse Override)
<b>Dusk Till Dawn</b>	No
<b>Multiple Unit Support</b>	Up to 4 Units In Parallel
<b>Cable Entry(s)</b>	Back Entry, Bottom Entry

### General

<b>Weight (g)</b>	193
<b>Height (mm)</b>	95
<b>Width (mm)</b>	78
<b>Depth (mm)</b>	141
<b>Body Construction</b>	Polycarbonate
<b>Product Colour</b>	Black
<b>Accessories (Included)</b>	Fittings (Rawl Plugs, Screws)
<b>EAN Number</b>	5012483013205
<b>Guarantee Period</b>	3 Years
<b>Trade Tariff Commodity Code</b>	8536508090

### Line Diagrams

