

# WFPIRWH

## Wi-Fi PIR Sensor With Direct / Indirect Switching - White

### Features & Benefits

- Adjustable time delay settings in app or offline
- LUX (light level) adjustment – Day to Night
- Manual ON/OFF switching override
- IP55 weatherproof rating
- Simple and quick to fit terminal block connectors
- Continues to work offline with loss of a Wi-Fi connection
- Learn option for custom lux level activation



### Technical Data

<b>Operating Voltage</b>	230V AC
<b>Frequency</b>	50Hz
<b>Installation Type</b>	Surface
<b>WLAN-Standard</b>	802.11 b/g/n 2.4GHz
<b>Earth Class Rating</b>	Class I
<b>Operating Temperature</b>	0°C to 40°C
<b>Ingress Protection Rating</b>	IP55
<b>Setting Type</b>	WIFI or Locally
<b>Contact Type</b>	Normally Open
<b>Approved Mounting Height (m)</b>	2.5
<b>Motion Detection (m)</b>	Up to 12 (Fixed)
<b>Detection Angle</b>	140°
<b>VPN Support</b>	May Affect Pairing

<b>Program Modes</b>	Scenes (Time Control, Dusk / Dawn), Presence & Absence Modes
<b>Pan &amp; Tilt Adjustment</b>	50° Tilt Up/Down, 160° Pan Left/Right
<b>Switch Type</b>	Single Pole, Single Throw (SPST)
<b>Mounting Hole Centres (mm)</b>	55
<b>Standby Consumption</b>	<1W
<b>Number Of Channels</b>	1
<b>Switch Rating</b>	250W LED, 500W Fluorescent, 1000W Incandescent
<b>Shortest Switching Time</b>	30 Seconds
<b>ON Time Adjustment</b>	30 Seconds - 30 Minutes
<b>LUX Level</b>	10 to 2000
<b>Detection Range (m)</b>	12
<b>Permanent ON Facility</b>	Yes
<b>Dusk Till Dawn</b>	App Based
<b>Multiple Unit Support</b>	Yes
<b>Cable Entry(s)</b>	Back Entry, Bottom Entry

## General

<b>Weight (g)</b>	190
<b>Height (mm)</b>	88
<b>Width (mm)</b>	79
<b>Depth (mm)</b>	100
<b>Body Construction</b>	Polycarbonate
<b>Product Colour</b>	White
<b>Accessories (Included)</b>	Rawl Plugs, Screws
<b>EAN Number</b>	5012483015674
<b>Guarantee Period</b>	3 Years

# Data sheet

## WFPIRWH

Wi-Fi / Wi-Fi PIR Sensors

Trade Tariff Commodity Code

8536508090

### Line Diagrams

